

100mm - Round Ducting

plus Accessories and Terminals

Ø100mm PVC	Product Code	Free Area = 7,855mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960097	Round Duct - 350mm Long	0.1	0.2	0.5
	8960110	Round Duct - 1.0m Long	0.1	0.5	1.4
	8960140	Round Duct - 1.5m Long	0.2	0.8	2.1
	ENQ	Round Duct - 2m Long	0.2	1.0	2.8
	8960142	90° Bend	1.6	5.6	21.1
	8960143	45° Bend	0.6	2.1	8.2
	8960144	Tee Piece	n/a		
	8960031	Duct Connector	0.3	0.9	4.2
	8960145	Duct Connector with Backdraught Damper	7.1	25.0	44.9
	8960146	Fixing Bracket	n/a		
	8960188	Jubilee Clip - 55mm to 170mm	n/a		
	*8960227	Ceiling Metal Vent Diffuser - Extract	5.0	13.4	53.7
	*8960229	Ceiling Metal Vent Diffuser - Supply	6.2	16.5	66.5
	Product Code	Terminations	8l/s	15l/s	30l/s
	8960105	External Louvred Grille (Free Area; 3,809mm ²) - White 	1.7	6.0	19.8
	8960102	External Louvred Grille (Free Area; 3,809mm ²) - Brown 			
	8960104	External Louvred Grille (Free Area; 3,809mm ²) - Terracotta 			
	8960103	External Louvred Grille (Free Area; 3,809mm ²) - Beige 			
	8960107	External Cowled Grille (Free Area; 7,200mm ²) - White (With non-return flap) 	1.3	4.7	17.2
	8960106	External Cowled Grille (Free Area; 7,200mm ²) - Brown (With non-return flap) 			
	8960239	External Cowled Grille (Free Area; 7,200mm ²) - Terracotta (With non-return flap) 			
	8960223	External High-Rise Grille (Free Area; 6,499mm ²) - White 	0.0	0.1	4.2
	8960222	External High-Rise Grille (Free Area; 6,499mm ²) - Brown 			
	8960112	External Round Grille (Free Area; 4,007mm ²) - with fly screen	4.3	15.0	48.1
	8960079	External Mushroom Cowl	n/a		

*Pressure losses with control disc 10mm open.

100mm - Round Ducting

plus Accessories and Terminals

Ø100mm PVC	Product Code	Free Area = 7,855mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960062	Round – 1m length	n/a		
	8960064	Round – 3m length	n/a		
	8960067	Round – 6m length	n/a		
	8960070	Round – 15m length	n/a		
	8960073	Round – 45m length	n/a		
	Product Code	Insulated Flexible	8l/s	15l/s	30l/s
	8960052	Aluminium – 5m length	n/a		
	8960051	Aluminium - 10m length	n/a		
	Product Code	Fire Protection	8l/s	15l/s	30l/s
	*8960228	Ceiling Metal Vent Diffuser - Extract with Fire Damper (Fire Rating 60 mins)	5.0	13.4	53.7
	QRS110	Ø100mm Fire Sleeve (Fire Rating 120 mins)	n/a		
	CFC100	CFC Ceiling Fan Cuff	n/a		
	FW100X100	Intumescent Wrap (Fire Rating 120 mins) to work with	n/a		
	FWS100X141	Metal Retaining Sleeve - for partition walls up to 132mm	n/a		
	Product Code	Insulation	8l/s	15l/s	30l/s
	89706	Insulation Jacket - 25mm Thick (10m Roll)	n/a		

*Pressure losses with control disc 10mm open.

125mm - Round Ducting

plus Accessories and Terminals

Ø125mm PVC	Product Code	Free Area = 12,273mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960114	Round Duct - 350mm Long	0.0	0.1	0.3
	8960115	Round Duct - 1.0m Long	0.1	0.2	0.7
	8960120	Round Duct - 1.5m Long	0.1	0.3	1.0
	8960161	Round Duct - 2m Long	0.1	0.4	1.4
	8960148	90° Bend	0.6	2.0	8.4
	8960149	45° Bend	0.2	0.7	2.9
	8960150	Tee Piece	n/a		
	8960184	Adaptor - Ø125mm to Ø100mm	0.4	1.5	5.9
	8960153	Duct Connector	0.1	0.2	0.9
	8960151	Duct Connector with Backdraught Damper	5.2	18.3	31.5
	8960251	Self Seal Connector - Duct to Duct	0.1	0.2	0.9
	8960373	Rapid Self Seal Connector - 90° Bend	0.5	1.3	7.0
	8960374	Rapid Self Seal Connector - T-Piece	n/a		
	8960152	Fixing Bracket	n/a		
	8960188	Jubilee Clip - 55mm to 170mm	n/a		
	*8960230	Ceiling Metal Vent Diffuser - Extract	6.0	12.6	36.4
	*8960232	Ceiling Metal Vent Diffuser - Supply	6.0	12.6	36.4
	*9030001	Ceiling Plastic Vent Diffuser - Extract	5.6	19	76
		Ceiling Plastic Vent Diffuser - Supply	4.5	15	60
	TP520	G3 Conical filter for Metal Extract Diffuser (8960230)	n/a		
	8960001	125mm Condensate Trap Kit	n/a		
	Product Code	Terminations	8l/s	15l/s	30l/s
	8960119	External Louvred Grille (Free Area; 6,123mm ²) - White 	1.3	4.6	18.4
	8960116	External Louvred Grille (Free Area; 6,123mm ²) - Brown 			
	8960118	External Louvred Grille (Free Area; 6,123mm ²) - Terracotta 			
	8960117	External Louvred Grille (Free Area; 6,123mm ²) - Beige 			
	8960134	External Cowled Grille (Free Area; 6,560mm ²) - White (With non-return flap) 	1.5	5.2	19.8
	8960132	External Cowled Grille (Free Area; 6,560mm ²) - Brown (With non-return flap) 			
	8960133	External Cowled Grille (Free Area; 6,560mm ²) - Terracotta (With non-return flap) 			

*Pressure losses with control disc 10mm open.

125mm - Round Ducting

plus Accessories and Terminals

Ø125mm PVC	Product Code	Free Area = 12,273mm ²	Static Pressure Drop (in Pa)		
		Flexible PVC Duct	8l/s	15l/s	30l/s
	8960063	Round – 1m length	n/a		
	8960065	Round – 3m length	n/a		
	8960068	Round – 6m length	n/a		
	8960071	Round – 15m length	n/a		
	Product Code	Insulated Flexible	8l/s	15l/s	30l/s
	8960054	Aluminium – 5m length	n/a		
	8960053	Aluminium - 10m length	n/a		
	Product Code	Fire Protection	8l/s	15l/s	30l/s
	*8960231	Ceiling Metal Vent Diffuser - Extract with Fire Damper (Fire Rating 60 mins)	6.0	12.6	36.4
	*8960233	Ceiling Metal Vent Diffuser - Supply with Fire Damper (Fire Rating 60 mins)	6.0	12.6	36.4
	QRS130	Ø125mm Fire Sleeve (Fire Rating 90 mins)	n/a		
	FSK125W	Intumescent Wrap & Sleeve Kit - for partition walls up to 132mm (Fire Rating 120 mins)	n/a		
	Product Code	Attenuation	8l/s	15l/s	30l/s
	CA125600	Galvanized Attenuator - 0.6m long (Ø235mm OD)	0.1	0.1	0.5
	CA125900	Galvanized Attenuator - 0.9m long (Ø235mm OD)	0.1	0.2	0.7
	CA1251200	Galvanized Attenuator - 1.2m long (Ø235mm OD)	0.1	0.3	0.9
	89720	Flexible Silencer - 0.5m long (Ø175mm OD)	n/a		
	89721	Flexible Silencer - 1.0m long (Ø175mm OD)	n/a		
	Product Code	Insulation	8l/s	15l/s	30l/s
	89701	Insulation Jacket - 25mm Thick (10m Roll)	n/a		
	8960299	Round Thermal Duct with connector - 1.0m Long	0.1	0.2	0.8
	8960300	Round Thermal Duct with connector - 2.0m Long	0.2	0.5	1.7
	8960303	Thermal 90° Bend with connectors	0.4	1.3	4.9
	8960304	Thermal 45° Bend with connectors	0.1	0.4	1.5
	8960305	Thermal Tee Piece with connectors	n/a		
	8960306	Thermal Self Seal Connector - Duct to Duct	0.1	0.2	0.9
	8960307	Thermal Self Seal Connector - Duct to Fitting	0.1	0.2	0.9

*Pressure losses with control disc 10mm open.

150mm - Round Ducting

plus Accessories and Terminals

Ø150mm PVC	Product Code	Free Area = 12,273mm ²	Static Pressure Drop (in Pa)		
		Components	30l/s	60l/s	90l/s
	8960191	Round Duct - 350mm Long	0.1	0.4	0.9
	8960192	Round Duct - 1.0m Long	0.4	1.2	2.7
	8960193	Round Duct - 1.5m Long	0.6	1.8	4.1
	ENQ	Round Duct - 2m Long	0.8	2.4	5.4
	8960155	90° Bend	4.2	18.2	41.0
	8960296	45° Bend	1.2	4.8	10.8
	8960156	Tee Piece	n/a		
	8960190	Adaptor - Ø150mm to Ø125mm	2.2	8.8	19.8
	8960158	Duct Connector	0.2	1.1	2.5
	8960157	Duct Connector with Backdraught Damper	23.5	43.6	98.1
	8960188	Jubilee Clip - 55mm to 170mm	n/a		
	*8960234	Ceiling Metal Vent Diffuser - Extract	3.5	12.5	49.6
	*8960235	Ceiling Metal Vent Diffuser - Supply	4.0	14.5	57.4
	TP521	G3 Conical filter with Metal Extract Diffuser (8960234)	n/a		
	8960002	150mm Condensate Trap Kit	n/a		
	Product Code	Terminations	30l/s	60l/s	90l/s
	8960130	External Louvred Grille (Free Area; 11,440mm ²) - White 	3.0	12.3	27.7
	8960126	External Louvred Grille (Free Area; 11,440mm ²) - Brown 			
	8960129	External Louvred Grille (Free Area; 11,440mm ²) - Terracotta 			
	8960127	External Louvred Grille (Free Area; 11,440mm ²) - Beige 			

*Pressure losses with control disc 10mm open.

150mm - Round Ducting

plus Accessories and Terminals

Ø150mm PVC	Product Code	Free Area = 12,273mm ²	Static Pressure Drop (in Pa)		
		Flexible PVC Duct	30l/s	60l/s	90l/s
	8960061	Round – 1m length	n/a		
	8960066	Round – 3m length	n/a		
	8960069	Round – 6m length	n/a		
	8960072	Round – 15m length	n/a		
	Product Code	Insulated Flexible	30l/s	60l/s	90l/s
	8960056	Aluminium – 5m length	n/a		
	8960055	Aluminium - 10m length	n/a		
	Product Code	Fire Protection	30l/s	60l/s	90l/s
	*8960274	Ceiling Metal Vent Diffuser - Extract with Fire Damper (Fire Rating 60 mins)	3.5	12.5	49.6
	*8960275	Ceiling Metal Vent Diffuser - Supply with Fire Damper (Fire Rating 60 mins)	4.0	14.5	57.4
	FSK150C	Intumescent Fire Cuff - for partition walls up to 132mm (Fire Rating 90 mins)	n/a		
	Product Code	Attenuation	30l/s	60l/s	90l/s
	CA150600	Galvanized Attenuator - 0.6m long (Ø270mm OD)	0.4	1.0	2.3
	89722	Flexible Silencer - 0.5m long (Ø200mm OD)	n/a		
	89723	Flexible Silencer - 1.0m long (Ø200mm OD)	n/a		
	Product Code	Insulation	30l/s	60l/s	90l/s
	89702	Insulation Jacket - 25mm Thick (10m Roll)	n/a		
Ø160mm PVC	Product Code	Free Area = 20,106mm ²	Static Pressure Drop (in Pa)		
		Insulation	30l/s	60l/s	90l/s
	8960327	Round Thermal Duct with connector - 1.0m Long	0.3	1.1	2.5
	8960328	Round Thermal Duct with connector - 2.0m Long	0.5	2.0	4.3
	8960329	Thermal 90° Bend with connectors	1.5	5.7	12.7
	8960330	Thermal 45° Bend with connectors	0.4	1.6	3.6
	8960331	Thermal Tee Piece with connectors	n/a		
	8960335	Thermal - Ø160mm to Ø150mm Adaptor	0.2	1.1	2.5
	8960332	Thermal Self Seal Connector - Duct to Duct	0.2	1.1	2.5
	8960333	Thermal Self Seal Connector - Duct to Fitting	0.2	1.1	2.5

*Pressure losses with control disc 10mm open.

204x60mm - Rectangular Ducting

plus Accessories and Terminals

204x60mm PVC	Product Code	Free Area = 11,452mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960162	Rectangular Duct - 0.5m Long	0.1	0.3	1.0
	8960163	Rectangular Duct - 1.0m Long	0.1	0.5	2.0
	8960176	Rectangular Duct - 1.5m Long	0.2	0.8	3.0
	8960177	Rectangular Duct - 2m Long	0.3	1.1	3.9
	8960164	90° Bend - Horizontal	0.5	1.8	7.5
	8960172	45° Bend - Horizontal	0.2	0.6	2.7
	8960168	90° Bend - Vertical	0.3	1.1	4.5
	8960173	45° Bend - Vertical	0.2	0.6	2.7
	8960178	Tee Piece	n/a		
	8960166	Duct Connector	0.0	0.1	0.3
	8960252	Self Seal Connector - Duct to Duct	0.1	0.2	0.9
	8960253	Self Seal Connector - Duct to Fitting	0.1	0.2	0.9
	8960369	Rapid Self Seal Connector - Horizontal Self-Seal T-piece	n/a		
	8960167	Fixing Bracket	n/a		
	8960006	Cross-Over Piece	0.2	0.7	2.9
	8960169	204x60mm to Ø125mm Horizontal Adaptor	0.3	1.0	3.8
	8960174	204x60mm to Ø100mm Vertical Adaptor	0.4	1.4	5.3
	8960165	204x60mm to Ø125mm Vertical Adaptor	0.5	1.7	6.9
	8960175	204x60mm to Ø150mm Vertical Adaptor	0.5	1.8	7.4
	Product Code	Terminations	8l/s	15l/s	30l/s
	TA350/392	Hi Flow Air Brick (Free Area; 8,670mm ²) - White 	0.6	2.2	7.8
	TA350/315	Hi Flow Air Brick (Free Area; 8,670mm ²) - Brown 			
	TA350/094	Hi Flow Air Brick (Free Area; 8,670mm ²) - Terracotta 			
	TA350/093	Hi Flow Air Brick (Free Area; 8,670mm ²) - Beige 			
	TA350/010	Hi Flow Air Brick (Free Area; 8,670mm ²) - Grey 			
	Product Code	Terminations	15l/s	30l/s	60l/s
	8960343	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - White 	0.9	3.30	8.40
	8960341	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Brown 			
	8960340	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Terracotta 			
	8960344	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Beige 			

204x60mm - Rectangular Ducting

plus Accessories and Terminals

204x60mm PVC	Product Code	Free Area = 11,452mm ²	Static Pressure Drop (in Pa)		
		Flexible PVC Duct	8l/s	15l/s	30l/s
	8960075	Rectangular – 1m length	n/a		
	8960077	Rectangular – 3m length	n/a		
	Product Code	Fire Protection	8l/s	15l/s	30l/s
	QRS205/60	204x60mm Fire Sleeve (Fire Rating 120 mins)	n/a		
	QRS204/60SS	204x60mm Fire Slim Sleeve (Fire Rating 90 mins)	n/a		
	FW204X60X100	Intumescent Wrap (Fire Rating 120 mins) to work with	n/a		
	FWS204X60X141	Metal Retaining Sleeve - for partition walls up to 132mm	n/a		
	Product Code	Attenuation	8l/s	15l/s	30l/s
	8960256	Cross-Talk Silencer - 0.5m Long (Free Area; 5,264mm ²)	2.9	10.5	18.5
	8960242	Cross-Talk Silencer - 1.0m Long (Free Area; 5,264mm ²)	3.0	10.4	17.2
	8960257	Cross-Talk Silencer - 1.5m Long (Free Area; 5,264mm ²)	2.3	8.2	23.5
	8960290	Hi-Flow Attenuator - 0.5m Long (Free Area; 11,664mm ²)	0.4	1.5	7.8
	8960291	Hi-Flow Attenuator - 1.0m Long (Free Area; 11,664mm ²)	0.5	1.8	8.0
	8960292	Hi-Flow Attenuator - 1.5m Long (Free Area; 11,664mm ²)	0.6	2.0	9.3
	Product Code	Insulation	8l/s	15l/s	30l/s
	89703	Insulation Jacket - 25mm Thick (10m Roll)	n/a		
	8960308	Rectangular Thermal Duct with connector - 1.0m Long	0.2	0.5	1.6
	8960309	Rectangular Thermal Duct with connector - 2.0m Long	0.0	0.5	2.6
	8960310	Thermal 90° Horizontal Bend with connectors	0.0	0.9	4.7
	8960311	Thermal 45° Horizontal Bend with connectors	0.0	0.0	1.3
	8960313	Thermal 90° Vertical Bend with connectors	0.0	0.6	3.6
	8960314	Thermal 45° Vertical Bend with connectors	0.0	0.0	0.4
	8960312	Thermal Tee Piece with connectors	n/a		
	8960315	Thermal 204x60mm to Ø125mm Plenum Adaptor	0.5	2.1	7.9
	8960316	Thermal Self Seal Connector - Duct to Duct	0.0	0.1	0.3
	8960317	Thermal Self Seal Connector - Duct to Fitting	0.0	0.1	0.3

220x90mm - Rectangular Ducting

plus Accessories and Terminals

220x90mm PVC	Product Code	Free Area = 18,545mm ²	Static Pressure Drop (in Pa)		
		Components	30l/s	60l/s	90l/s
	8960012	Rectangular Duct - 1.0m Long	0.3	1.2	2.7
	8960013	Rectangular Duct - 1.5m Long	0.4	1.7	3.8
	8960247	Rectangular Duct - 2m Long	0.5	2.3	4.4
	8960017	90° Bend - Horizontal	1.8	7.3	16.4
	8960019	45° Bend - Horizontal	0.6	2.4	5.4
	8960022	90° Bend - Vertical	1.6	6.2	14.0
	8960024	45° Bend - Vertical	0.5	1.9	4.3
	8960020	Tee Piece	n/a		
	8960014	Duct Connector	0.0	0.0	0.0
	8960270	Self-Seal - Duct Connector (Duct-to-Duct)	0.0	0.0	0.0
	8960271	Self-Seal - Duct Connector (Duct-to-Fitting)	0.0	0.0	0.0
	8960370	Rapid Self-Seal - Duct Connector Horizontal Self-Seal T-Piece	n/a		
	8960372	Rapid Self-Seal - Duct Connector 90° Bend Self-Seal	4.2	16.8	enq
	8960015	Fixing Bracket	n/a		
	8960025	220x90mm to Ø150mm Horizontal Adaptor	0.4	1.7	3.8
	8960021	220x90mm to 204x60mm Horizontal Adaptor	3.7	14.7	33.1
	8960016	220x90mm to Ø100mm Vertical Adaptor	n/a		
	8960018	220x90mm to Ø125mm Vertical Adaptor	5.8	23.0	51.8
	8960023	220x90mm to Ø150mm Vertical Adaptor	2.7	10.6	23.9
	Product Code	Terminations	30l/s	60l/s	90l/s
	8960011	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - White 	2.1	8.5	19.1
	8960008	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Brown 			
	8960010	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Terracotta 			
	8960009	Double Airbrick Adapter with Grilles (Free Area; 15,360mm ²) - Beige 			

220x90mm - Rectangular Ducting

plus Accessories and Terminals

220x90mm PVC	Product Code	Free Area = 18,545mm ²	Static Pressure Drop (in Pa)		
		Flexible PVC Duct	30l/s	60l/s	90l/s
	8960078	Rectangular – 3m length	n/a		
	Product Code	Fire Protection	30l/s	60l/s	90l/s
	QRS220/90	220x90mm Fire Sleeve (Fire Rating 120 mins)	n/a		
	QRS220/90SS	220x90mm Fire Slim Sleeve (Fire Rating 60 mins)	n/a		
	FSK220X90X132W	Intumescent Fire Wrap Kit - for partition walls up to 132mm (Fire Rating 60 mins)	n/a		
	Product Code	Attenuation	30l/s	60l/s	90l/s
	8960293	Hi-Flow Attenuator - 0.5m Long (Free Area; 11,664mm ²)	2.9	11.7	26.3
	8960294	Hi-Flow Attenuator - 1.0m Long (Free Area; 11,664mm ²)	3.5	13.8	31.0
	8960295	Hi-Flow Attenuator - 1.5m Long (Free Area; 11,664mm ²)	4.3	17.0	38.3
	Product Code	Insulation	30l/s	60l/s	90l/s
	89704	Insulation Jacket - 25mm Thick (10m Roll)	n/a		
	8960318	Rectangular Thermal Duct with connector - 1.0m Long	0.4	1.5	3.1
	8960319	Rectangular Thermal Duct with connector - 2.0m Long	0.9	3.2	6.8
	8960320	Thermal 90° Horizontal Bend with connectors	1.9	6.9	15.2
	8960321	Thermal 45° Horizontal Bend with connectors	0.5	2.1	4.8
	8960323	Thermal 90° Vertical Bend with connectors	1.7	6.4	14.2
	8960324	Thermal 45° Vertical Bend with connectors	0.2	1.0	2.3
	8960322	Thermal Tee Piece with connectors	n/a		
	8960334	Thermal 220x90mm to Ø125mm Plenum Adaptor	8.4	30.8	67.1
	8960325	Thermal Self Seal Connector - Duct to Duct	0.2	0.8	2.0
	8960326	Thermal Self Seal Connector - Duct to Fitting	0.2	0.8	2.0

110x54mm - Rectangular Ducting

plus Accessories and Terminals

110x54mm PVC	Product Code	Free Area = 5,424mm ²	Static Pressure Drop (in Pa)		
		Components	8l/s	15l/s	30l/s
	8960109	Rectangular Duct - 1.0m Long	0.6	2.2	8.6
	8960096	Rectangular Duct - 1.5m Long	0.9	3.3	12.8
	ENQ	Rectangular Duct - 2m Long	1.2	4.4	17.1
	8960094	90° Bend - Horizontal	2.8	9.8	39.8
	8960081	45° Bend - Horizontal	1.1	3.7	15.5
	8960095	90° Bend - Vertical	4.4	15.6	62.8
	8960003	45° Bend - Vertical	0.7	2.6	12.7
	8960082	Tee Piece	n/a		
	8960091	Duct Connector	0.1	0.3	1.4
	8960131	Flexible Duct Connector	0.1	0.3	1.4
	8960084	Fixing Bracket	n/a		
	8960108	110x54mm to 204x60mm Horizontal Adaptor	n/a		
	8960111	110x54mm to Ø100mm Horizontal Adaptor	1.1	3.7	14.6
	8960080	110x54mm to Ø100mm Horizontal Short Adaptor - Male	1.4	4.8	20.4
	8960093	110x54mm to Ø100mm Vertical Adaptor - Male	2.3	8.1	33.1
	8960092	110x54mm to Ø100mm Vertical Adaptor - Female	2.3	8.1	33.1
	Product Code	Terminals	8l/s	15l/s	30l/s
	8960089	External Louvred Grille (Free Area; 2,600mm ²) - Brown 	4.3	15.0	48.1
	8960090	External Louvred Grille (Free Area; 2,600mm ²) - Terracotta 			
	8960088	External Cowled Grille (Free Area; 5,800mm ²) - White 	2.4	8.4	30.4
	8960085	External Cowled Grille (Free Area; 5,800mm ²) - Brown 			
	8960086	External Cowled Grille (Free Area; 5,800mm ²) - Beige 			
	8960087	External Cowled Grille (Free Area; 5,800mm ²) - Terracotta 			
	Product Code	Flexible PVC Duct	8l/s	15l/s	30l/s
	8960074	Rectangular – 1m length	n/a		
	8960076	Rectangular – 3m length	n/a		
	Product Code	Fire Protection	8l/s	15l/s	30l/s
	QRS110/54	110x54mm Fire Sleeve (Fire Rating 120 mins)	n/a		
	QRS110/54SS	110x54mm Fire Slim Sleeve (Fire Rating 120 mins)	n/a		
	FW110X54X100	Intumescent Wrap (Fire Rating 120 mins) to work with	n/a		
	FWS110X54X141	Metal Retaining Sleeve - for partition walls up to 132mm	n/a		